

YARGUS 



Rotary Drum Blend Systems by **YARGUS**

Yargus Rotary Drum Blend Systems feature the fastest discharge rate in the industry - four tons per minute - and an extra large flared opening for easier, faster, cleaner loading.

Rotary Drum Blend Systems

The 20,000-pound capacity trunnion wheels distribute the load for smooth, efficient blending, and the solid construction assures years of dependable service.

- Available in 13- and 16-ton capacities
- 38" stainless steel mixing auger is standard on 13- & 16-Ton
- Fast 6-tons per minute discharge rate on 13- & 16-Ton
- Direct drive is standard on 13- & 16-Ton, and optional on 6-, 8- & 10-Ton
- Remote control options
- Adjustable deflector available on transfer conveyor for straight product loads

Safety Features:

The modular design allows easy add-ons creating a system with a variety of hopper sizes.

- Independent safety guard covers belt and chain assembly
- Deflector
- Manhole clearout
- 13- and 16-ton trunnion wheel guard
- Shaft and coupling guard



YARGUS

12285 E. Main Street Marshall, IL 62441 USA
217.826.6352 layco@yargus.com yargus.com

AGI

YARGUS 



Designed by **YARGUS** For Space And Loading Efficiency

Yargus offers two vertical blenders that are designed for more efficient loading and unloading. Solid construction assures years of dependable service.

Tapered Auger Vertical Blend Systems

Features an innovative flat-front design for lower dump height, a larger loader hopper for efficient loading, and a lower center of gravity for better stability.

- Available in 6-, 8-, 10-, 13-, 16- and 18-ton capacities

Single-Unit Open Top Blends Systems

Blends more quickly than most conventional and competitive blenders. The Yargus original blender is simple to operate and unloads rapidly in four different directions.

- 5- and 6-ton models feature a single auger
- 8- and 10- ton models feature a double auger
- 15-ton models offer larger hoppers with a double auger



12285 E. Main Street Marshall, IL 62441 USA
217.826.6352 layco@yargus.com yargus.com

